Nonmetallic Hose Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4720-00-904-6608

Cross Sectio	onal Shape:
Round	
Thread Direc	tion:
Right-hand 1s	st end
Inside Diame	eter:
Between 0.17	2 inches and 0.188 inches
Tempurature	Rating:
-40.0 degrees	s fahrenheit and 200.0 degrees fahrenheit single response
Outside Dian	neter:
Between 0.35	59 inches and 0.375 inches
Connection S	Style:
Swivel, plain	2nd end
End Connect	tion Design:
Straight 2nd e	and
Connection <sup>-</sup>	Туре:
Threaded exte	ernal pipe 2nd end
Burst Test P	ressure:
2000.0 pound	ds per square inch
Layer Compo	osition And Location:
1st layer rubb	per impregnated cotton fabric and outer layer molded rubber, chloroprene
Maximum Op	perating Pressure:
500.0 pounds	s per square inch
Thread Size:	
0.125 inches	2nd end
Hydrostatic <sup>-</sup>	Test Pressure:
1000.0 pound	ls per square inch
Inside Surfac	ce Condition:
Smooth	
Measuring M	lethod And Length:
16.375 inches	s and 16.500 inches
Thread Serie	es Designator:
Npt 1st end	
Shelf Life:	
N/a	
Unit Of Meas	sure:
Demilitarizat	ion:
No	
Fiig:	
A542a0	
Fiig:	