NSN 4720-00-905-1885

Round

Thread Class: 3b 1st end

Thread Direction:



Nonmetallic Hose Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4720-00-905-1885 **Cross Sectional Shape:**

Right-hand 1st end					
Inside Diameter:					
0.188 inches					
Tempurature Rating:					
-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response					
Outside Diameter:					
0.312 inches					
Minimum Inside Bending Radius:					
2.000 inches					
Connection Style:					
Swivel nut flare 1st end					
End Connection Design:					
Straight 1st end					
Connection Type:					
Threaded internal tube 1st end					
Features Provided:					
Electrostatic discharge capability					
Burst Test Pressure:					
12000.0 pounds per square inch					
Layer Composition And Location:					
Outer layer braided corrosion resistant steel wire					
Maximum Operating Pressure:					
1500.0 pounds per square inch					
Thread Size:					
0.375 inches 1st end					
Seat Angle:					
37.0 degrees 1st end					
Hydrostatic Test Pressure:					
3000.0 pounds per square inch					
Outer Covering Environmental Protection:					
Corrosion resistant					
Vacuum In Torr:					
50.8					
Inside Surface Condition:					
Smooth					
Measuring Method And Length:					
9.500 inches working					

NSN 4720-00-905-1885

Nonmetallic Hose Assembly - Page 2 of 2



		•		
Ιh	read	Series	Desiar	າator:

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0