## NSN 4720-00-905-1968

Unf 2nd end

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-905-1968

| Cross Sectional Shape:  |
|---|
| Round   |
| Thread Class:   |
| 3b 1st end  |
| Thread Direction:   |
| Right-hand 1st end  |
| Inside Diameter:  |
| 0.125 inches  |
| Tempurature Rating:   |
| -67.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response |
| Outside Diameter:   |
| 0.268 inches  |
| Minimum Inside Bending Radius:  |
| 1.500 inches  |
| Connection Style:   |
| Swivel nut flare 2nd end  |
| End Connection Design:  |
| Straight 1st end  |
| Connection Type:  |
| Threaded internal tube 1st end  |
| Burst Test Pressure:  |
| 7500.0 pounds per square inch   |
| Layer Composition And Location:   |
| Outer layer braided corrosion resistant steel wire                                    |
| Maximum Operating Pressure:   |
| 1500.0 pounds per square inch   |
| Thread Size:  |
| 0.375 inches 1st end  |
| Seat Angle:   |
| 37.0 degrees 2nd end  |
| Hydrostatic Test Pressure:  |
| 3000.0 pounds per square inch   |
| Flow Angle:   |
| 90.0 degrees 2nd end  |
| Vacuum In Torr:   |
| 50.8  |
| Inside Surface Condition:   |
| Smooth  |
| Measuring Method And Length:  |
| 68.000 inches working   |
| Thread Series Designator:   |

## NSN 4720-00-905-1968

Nonmetallic Hose Assembly - Page 2 of 2



| Specification Data | Spe | ecifica | ition | Data: |
|--------------------|-----|---------|-------|-------|
|--------------------|-----|---------|-------|-------|

96906-ms8005 government standard

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0