

View Online at <https://aerobasegroup.com/nsn/4720-00-905-6233>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

Between 0.235 inches and 0.250 inches

Temperature Rating:

-450.0 degrees fahrenheit single response and 1200.0 degrees fahrenheit single response

Outside Diameter:

Between 0.429 inches and 0.439 inches

Minimum Inside Bending Radius:

6.250 inches

Inner Conveying Tube Style:

Annular close-pitch corrugated

Exterior Color:

Natural

Connection Style:

Swivel nut flare 2nd end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Burst Test Pressure:

9800.0 pounds per square inch

Layer Composition And Location:

Outer layer braided corrosion resistant steel wire

Maximum Operating Pressure:

1625.0 pounds per square inch

Thread Size:

0.438 inches 1st end

Seat Angle:

37.0 degrees 2nd end

Hydrostatic Test Pressure:

3250.0 pounds per square inch

Flow Angle:

90.0 degrees 2nd end

Outer Covering Environmental Protection:

Corrosion resistant

Measuring Method And Length:

15.000 inches

Thread Series Designator:

Unf 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0