

View Online at <https://aerobasegroup.com/nsn/4720-00-909-1984>

Cross Sectional Shape:

Round

Inside Diameter:

0.875 inches

Temperature Rating:

-65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response

Flange Thickness:

0.297 inches 2nd end

Outside Diameter:

1.031 inches

Minimum Inside Bending Radius:

7.375 inches

Exterior Color:

Natural

Center To Center Distance Between Bolt Holes Along Width:

1.656 inches 1st end

Center To Center Distance Between Bolt Holes Along Length:

1.656 inches 1st end

Bolt Hole Quantity:

4 2nd end

Flange Length:

2.188 inches 1st end

Flange Width:

2.188 inches 1st end

Connection Style:

Raised swivel 2nd end

Bolt Hole Diameter:

0.266 inches 1st end

Raised Face Height:

0.018 inches 2nd end

Raised Face Diameter:

1.884 inches 1st end

End Flange Construction:

Solid 2nd end

End Connection Design:

Straight 2nd end

Connection Type:

Raised face flange 2nd end

Features Provided:

Electrostatic discharge capability

Burst Test Pressure:

4000.0 pounds per square inch

Layer Composition And Location:

1st layer braided corrosion resistant steel wire and outer layer braided corrosion resistant steel wire

Maximum Operating Pressure:

250.0 pounds per square inch

Hydrostatic Test Pressure:

2000.0 pounds per square inch

Outer Covering Environmental Protection:

Corrosion resistant

Vacuum In Torr:

50.8

Inside Surface Condition:

Smooth

Measuring Method And Length:

25.500 inches working

Flange Style:

Rectangular (includes square) 2nd end

Supplementary Features:

This item has been reviewed for asbestos material; the current approved sources, 50599, 98441 and 78570 have indicated their part number contained asbestos prior to 1984, they continue to manufacture the same part number without asbestos material after 1984

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0