## NSN 4720-00-910-0864

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-910-0864

Cross Sectional Shape:					
Round					
Thread Class:					
3b 1st end					
Thread Direction:					
Right-hand 1st end					
Inside Diameter:					
0.500 inches					
Tempurature Rating:					
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response					
Outside Diameter:					
0.750 inches					
Minimum Inside Bending Radius:					
5.000 inches					
Connection Style:					
Swivel nut flare 1st end					
End Connection Design:					
Straight 2nd end					
Connection Type:					
Threaded internal tube 1st end					
Burst Test Pressure:					
1000.0 pounds per square inch					
Layer Composition And Location:					
1st layer braided cotton cord and outer layer braided cotton cord					
Maximum Operating Pressure:					
250.0 pounds per square inch					
Thread Size:					
0.750 inches 1st end					
Seat Angle:					
37.0 degrees and 45.0 degrees 1st end					
Outer Covering Environmental Protection:					
Mildew resistant and oil resistant					
Vacuum In Torr:					
50.8					
Inside Surface Condition:					
Smooth					
Measuring Method And Length:					
30.000 inches					
Media For Which Designed:					
Fuel/oil, hydrocarbon and water single response					
Thread Series Designator:					

Unf 1st end

## NSN 4720-00-910-0864

Nonmetallic Hose Assembly - Page 2 of 2



_				
c	hο	JIF.		ife:
J			_	HG.

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0