

View Online at <https://aerobasegroup.com/nsn/4720-00-911-1605>

**Cross Sectional Shape:**

Round

**Thread Class:**

3a 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.440 inches

**Temperature Rating:**

-450.0 degrees fahrenheit single response

**Outside Diameter:**

0.800 inches

**Minimum Inside Bending Radius:**

8.000 inches

**Connection Style:**

External seat for gasket seal (boss) 1st end

**End Connection Design:**

Straight 1st end

**Connection Type:**

Threaded external boss 1st end

**Features Provided:**

Electrostatic discharge capability

**Thready Qty Per Inch (tpi):**

12 1st end

**Second End Relationship With First End:**

Identical

**Burst Test Pressure:**

24000.0 pounds per square inch

**First End Swivel Action Capability:**

Not included

**Layer Composition And Location:**

Outer layer braided corrosion resistant steel wire err-100

**Maximum Operating Pressure:**

6000.0 pounds per square inch

**Thread Size:**

1.750 inches 1st end

**Hydrostatic Test Pressure:**

1200.0 pounds per square inch

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

15.500 inches

**Special Features:**

Inner conveying tube material-plastic, polytetrafluoroethylene

**Thread Series Designator:**

Un 1st end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0