NSN 4720-00-911-3977

Fuel/oil, hydrocarbon single response

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-911-3977

Cross Sectional Shape:
Round
Thread Class:
2a 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.440 inches
Tempurature Rating: 65.0 degrees fabrophoit, and 450.0 degrees fabrophoit single response
-65.0 degrees fahrenheit and 450.0 degrees fahrenheit single response Outside Diameter:
0.800 inches
Minimum Inside Bending Radius:
8.000 inches
Exterior Color:
Natural
Connection Style:
External seat for gasket seal (boss) 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded external boss 1st end
Thready Qty Per Inch (tpi):
12 1st end
Burst Test Pressure:
18000.0 pounds per square inch
Layer Composition And Location:
1st layer braided corrosion resistant steel wire and 2nd layer braided corrosion resistant steel wire and outer layer braided corrosion
resistant steel wire
Maximum Operating Pressure:
4500.0 pounds per square inch
Thread Size:
1.750 inches 1st end
Hydrostatic Test Pressure:
9000.0 pounds per square inch
Outer Covering Environmental Protection:
Corrosion resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
23.625 inches
Media For Which Designed:

NSN 4720-00-911-3977

Nonmetallic Hose Assembly - Page 2 of 2



No

Fiig:

A542a0