## NSN 4720-00-912-3873

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-912-3873

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
Between 0.244 inches and 0.266 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
Between 0.469 inches and 0.516 inches
Minimum Inside Bending Radius:
2.000 inches
Exterior Color:
Black
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
1600.0 pounds per square inch
Layer Composition And Location:
1st layer rubber impregnated braided fabric and outer layer molded rubber, chloroprene
Maximum Operating Pressure:
400.0 pounds per square inch
Thread Size:
0.438 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
800.0 pounds per square inch
Outer Covering Environmental Protection:
Abrasion resistant and fuel resistant and hydraulic solution resistant and oil resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
9.500 inches working
Thread Series Designator:
Unjf 1st end

## NSN 4720-00-912-3873

Nonmetallic Hose Assembly - Page 2 of 2



Shel	fli	fo.
Olici		ıc.

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0