NSN 4720-00-912-4613

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-912-4613 **Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.312 inches **Tempurature Rating:** -65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response **Outside Diameter:** 0.688 inches **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end **Burst Test Pressure:** 10000.0 pounds per square inch **Layer Composition And Location:** 1st layer braided steel wire and outer layer molded rubber **Maximum Operating Pressure:** 2500.0 pounds per square inch **Thread Size:** 0.625 inches 1st end Seat Angle: 45.0 degrees 1st end **Hydrostatic Test Pressure:** 5000.0 pounds per square inch **Outer Covering Environmental Protection:** Oil resistant and ozone resistant and mildew resistant **Inside Surface Condition:** Smooth **Measuring Method And Length:**

22.000 inches

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

NSN 4720-00-912-4613

Nonmetallic Hose Assembly - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МА	261	ıre:

--

Demilitarization:

No

Fiig:

A542a0