## NSN 4720-00-912-4614

**Cross Sectional Shape:** 

Round

**Thread Class:** 

Unf 1st end

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-912-4614

| 2b 1st end  |
|---|
| Thread Direction:   |
| Right-hand 1st end  |
| Inside Diameter:  |
| 0.312 inches  |
| Tempurature Rating:   |
| -65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response |
| Outside Diameter:   |
| 0.688 inches  |
| Minimum Inside Bending Radius:  |
| 4.500 inches  |
| Connection Style:   |
| Swivel nut flare 1st end  |
| End Connection Design:  |
| Straight 1st end  |
| Connection Type:  |
| Threaded internal tube 1st end  |
| Burst Test Pressure:  |
| 10000.0 pounds per square inch  |
| Layer Composition And Location:                                       |
| 1st layer braided steel wire and outer layer molded rubber            |
| Maximum Operating Pressure:   |
| 2500.0 pounds per square inch   |
| Thread Size:  |
| 0.625 inches 1st end  |
| Seat Angle:   |
| 45.0 degrees 1st end  |
| Hydrostatic Test Pressure:  |
| 5000.0 pounds per square inch   |
| Outer Covering Environmental Protection:                              |
| Mildew resistant and oil resistant and oil resistant                  |
| Inside Surface Condition:   |
| Smooth  |
| Measuring Method And Length:  |
| 37.000 inches   |
| Media For Which Designed:   |
| Fuel/oil, hydrocarbon single response                                 |
| Thread Series Designator:   |

## NSN 4720-00-912-4614

Nonmetallic Hose Assembly - Page 2 of 2



| _  |   |   |    |    |    |
|----|---|---|----|----|----|
| ٠. | n | _ | I+ | 18 | e: |
|    |   |   |    |    |    |

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0