NSN 4720-00-912-5640



Nonmetallic Hose Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4720-00-912-5640 **Cross Sectional Shape:** Round **Thread Class:** 2b 1st end **Thread Direction:** Right-hand 1st end **Tempurature Rating:** -65.0 degrees fahrenheit and 300.0 degrees fahrenheit single response **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end Thready Qty Per Inch (tpi): 18 1st end **Burst Test Pressure:** 4000.0 pounds per square inch **Layer Composition And Location:** 1st layer braided cotton cord and 2nd layer braided steel wire and outer layer molded rubber, chloroprene **Maximum Operating Pressure:** 1000.0 pounds per square inch **Thread Size:** 0.562 inches 1st end Seat Angle: 37.0 degrees 1st end **Hydrostatic Test Pressure:** 2000.0 pounds per square inch **Inside Surface Condition:** Smooth **Measuring Method And Length:** 8.000 inches working Media For Which Designed: Fuel/oil, hydrocarbon single response **Thread Series Designator:** Unf 1st end Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No

NSN 4720-00-912-5640

Nonmetallic Hose Assembly - Page 2 of 2



Fiig:

A542a0