## NSN 4720-00-912-6682

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-912-6682

Cross Sectional Shape:				
Round				
Thread Class:				
2b 1st end				
Thread Direction:				
Right-hand 1st end				
Inside Diameter:				
0.375 inches				
Tempurature Rating:				
-65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response				
Outside Diameter:				
0.594 inches				
Exterior Color:				
Natural				
Connection Style:				
Swivel nut flare 1st end				
End Connection Design:				
Straight 2nd end				
Connection Type:				
Threaded internal tube 1st end				
Thready Qty Per Inch (tpi):				
18 2nd end				
Burst Test Pressure:				
1000.0 pounds per square inch				
Layer Composition And Location:				
1st layer braided cotton cord and outer layer molded rubber, synthetic				
Maximum Operating Pressure:				
250.0 pounds per square inch				
Thread Size:				
0.625 inches 1st end				
Seat Angle:				
45.0 degrees 1st end				
Hydrostatic Test Pressure:				
500.0 pounds per square inch				
Outer Covering Environmental Protection:				
Fuel resistant and mildew resistant and oil resistant and ozone resistant and cold resistant				
Inside Surface Condition:				
Smooth				
Measuring Method And Length:				
21.156 inches				
Media For Which Designed:				
Fire I/e II have described a six also recorded				

Fuel/oil, hydrocarbon single response

## NSN 4720-00-912-6682

Nonmetallic Hose Assembly - Page 2 of 2



_	brood	Carias	Docionatori
ı	meau	Series	Designator:

Unf 1st end

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0