## NSN 4720-00-913-0814

**Cross Sectional Shape:** 

Round

Thread Class: 3b 1st end

Thread Direction:
Right-hand 1st end
Inside Diameter:

**Tempurature Rating:** 

Between 0.321 inches and 0.398 inches

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-913-0814

-65.0 degrees fanrenneit and 200.0 degrees fanrenneit single response
Outside Diameter:
Between 0.477 inches and 0.641 inches
Minimum Inside Bending Radius:
2.500 inches
Exterior Color:
Black
Connection Style:
Swivel nut, flareless 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
600.0 pounds per square inch
Layer Composition And Location:
1st layer braided fabric and outer layer molded rubber, neoprene
Maximum Operating Pressure:
200.0 pounds per square inch
Thread Size:
0.562 inches 2nd end
Seat Angle:
12.0 degrees 2nd end
Hydrostatic Test Pressure:
400.0 pounds per square inch
Flow Angle:
90.0 degrees 2nd end
Outer Covering Environmental Protection:
Abrasion resistant and fuel resistant and light resistant and oil resistant and weatherproof
Inside Surface Condition:
Smooth
Measuring Method And Length:
24.000 inches

## NSN 4720-00-913-0814

Nonmetallic Hose Assembly - Page 2 of 2



Thread	<b>Series</b>	Design	nator:

Unf 2nd end

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0