## NSN 4720-00-913-2432

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-913-2432

Cross Sectional Shape:
Round

Thread Class:
3b 1st end

Thread Direction:
Right-hand 1st end
Inside Diameter:
0.219 inches

Tempurature Rating:
-65.0 degrees fahrenheit and 400.0 degrees fahrenheit single response

Outside Diameter:

Minimum Inside Bending Radius:

3.000 inches

0.469 inches

Connection Style:

Swivel nut, flareless 1st end

**End Connection Design:** 

Straight 1st end

**Connection Type:** 

Threaded internal tube 1st end

**Features Provided:** 

Electrostatic discharge capability

**Burst Test Pressure:** 

160.0 pounds per square inch

**Layer Composition And Location:** 

1st layer braided steel wire and 2nd layer spirally wrapped polytetrafluoroethylene fabric and outer layer braided corrosion resistant steel wire

**Maximum Operating Pressure:** 

3000.0 pounds per square inch

**Thread Size:** 

0.438 inches 1st end

Seat Angle:

12.0 degrees 1st end

**Hydrostatic Test Pressure:** 

8000.0 pounds per square inch

**Inside Surface Condition:** 

Smooth

**Measuring Method And Length:** 

14.500 inches working

**Thread Series Designator:** 

Unf 1st end

Shelf Life:

N/a

## NSN 4720-00-913-2432

Nonmetallic Hose Assembly - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A542a0