Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-913-3321

Round

Thread Class:

3b 1st end

# Thread Direction:

Right-hand 1st end

## Inside Diameter:

0.500 inches

#### **Tempurature Rating:**

-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

#### **Outside Diameter:**

0.969 inches

Minimum Inside Bending Radius:

#### 7.000 inches

**Exterior Color:** 

Black

### **Connection Style:**

Swivel nut flare 2nd end

#### **End Connection Design:**

Straight 1st end

## Connection Type:

Threaded internal tube 1st end

### **Features Provided:**

Reusable end fittings

### **Burst Test Pressure:**

14000.0 pounds per square inch

### Layer Composition And Location:

1st layer braided steel wire and 2nd layer braided steel wire and outer layer molded rubber, chloroprene

### Maximum Operating Pressure:

3500.0 pounds per square inch

### Thread Size:

0.750 inches 2nd end

#### Seat Angle:

37.0 degrees 2nd end

### Hydrostatic Test Pressure:

7000.0 pounds per square inch

### Flow Angle:

90.0 degrees 2nd end

## **Outer Covering Environmental Protection:**

Oil resistant and weatherproof

## Inside Surface Condition:

Smooth

Nonmetallic Hose Assembly - Page 2 of 2



Measuring Method And Length:

16.875 inches working and 17.250 inches working

**Thread Series Designator:** 

Unf 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0