

View Online at <https://aerobasegroup.com/nsn/4720-00-913-3934>

**Cross Sectional Shape:**

Round

**Thread Class:**

2b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.750 inches

**Temperature Rating:**

-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

**Flange Thickness:**

0.056 inches 2nd end

**Outside Diameter:**

Between 1.219 inches and 1.281 inches

**Minimum Inside Bending Radius:**

9.500 inches

**Center To Center Distance Between Bolt Holes Along Width:**

0.088 inches 2nd end

**Center To Center Distance Between Bolt Holes Along Length:**

1.875 inches 2nd end

**Bolt Hole Quantity:**

4 2nd end

**Flange Length:**

2.056 inches 2nd end

**Flange Width:**

2.007 inches 2nd end

**Connection Style:**

Swivel nut flare 1st end

**Bolt Hole Diameter:**

0.041 inches 2nd end

**Raised Face Diameter:**

1.500 inches 2nd end

**End Flange Construction:**

Solid 2nd end

**End Connection Design:**

Straight 1st end

**Connection Type:**

Threaded internal tube 1st end

**Features Provided:**

Electrostatic discharge capability

**Burst Test Pressure:**

9000.0 pounds per square inch

**Layer Composition And Location:**

1st layer braided steel wire and 2nd layer braided steel wire and outer layer molded rubber, chloroprene

**Maximum Operating Pressure:**

2250.0 pounds per square inch

**Thread Size:**

0.875 inches 1st end

**Seat Angle:**

37.0 degrees 1st end

**Hydrostatic Test Pressure:**

4500.0 pounds per square inch

**Flow Angle:**

45.0 degrees 2nd end

**Outer Covering Environmental Protection:**

Abrasion resistant and oil resistant and weatherproof

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

24.005 inches working

**Flange Style:**

Double oval (sae split type flange) 2nd end

**Thread Series Designator:**

Unf 1st end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0