## NSN 4720-00-913-6077

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-913-6077

| Cross Sectional Shape:   |
|--|
| Round  |
| Thread Class:  |
| 3b 1st end   |
| Thread Direction:  |
|  |
| Right-hand 1st end  Inside Diameter:   |
| 0.406 inches   |
|  |
| Tempurature Rating:  65.0 degrees februaries single response and 450.0 degrees februaries single response. |
| -65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response  Outside Diameter:   |
|  |
| 0.562 inches   |
| Connection Style:  |
| Swivel nut flare 1st end   |
| End Connection Design:   |
| Straight 1st end   |
| Connection Type:   |
| Threaded internal tube 1st end   |
| Burst Test Pressure:   |
| 8000.0 pounds per square inch  |
| Layer Composition And Location:  |
| Outer layer braided corrosion resistant steel wire   |
| Maximum Operating Pressure:  |
| 1500.0 pounds per square inch  |
| Thread Size:   |
| 0.750 inches 1st end   |
| Seat Angle:  |
| 37.0 degrees 1st end   |
| Hydrostatic Test Pressure:   |
| 3000.0 pounds per square inch  |
| Inside Surface Condition:  |
| Smooth   |
| Measuring Method And Length:   |
| 13.000 inches working  |
| Thread Series Designator:  |
| Unf 1st end  |
| Fsc Application Data:  |
| Jet engine, aircraft   |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |

--

## NSN 4720-00-913-6077

Nonmetallic Hose Assembly - Page 2 of 2



Demilitarization:

No

Fiig:

A542a0