

View Online at <https://aerobasegroup.com/nsn/4720-00-913-7945>

Cross Sectional Shape:

Round

Thread Class:

2b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

1.125 inches

Temperature Rating:

-25.0 degrees fahrenheit and 150.0 degrees fahrenheit single response

Flange Thickness:

0.620 inches 2nd end

Minimum Inside Bending Radius:

9.000 inches

Center To Center Distance Between Bolt Holes Along Width:

1.400 inches 2nd end

Center To Center Distance Between Bolt Holes Along Length:

2.750 inches 2nd end

Bolt Hole Quantity:

4 2nd end

Flange Length:

3.690 inches 2nd end

Flange Width:

3.254 inches 2nd end

Connection Style:

Swivel nut flare 1st end

Bolt Hole Diameter:

0.530 inches 2nd end

Raised Face Height:

0.020 inches 2nd end

Raised Face Diameter:

2.375 inches 2nd end

End Flange Construction:

Split 2nd end

End Connection Design:

Straight 2nd end

Connection Type:

Threaded internal tube 1st end

Features Provided:

Self-sealing

Thready Qty Per Inch (tpi):

12 1st end

Burst Test Pressure:

500.0 pounds per square inch

Layer Composition And Location:

1st layer braided cotton cord and 2nd layer braided steel wire and outer layer rubber impregnated braided cotton cord

Maximum Operating Pressure:

125.0 pounds per square inch

Thread Size:

1.625 inches 1st end

Seat Angle:

37.0 degrees 1st end

Outer Covering Environmental Protection:

Mildew resistant and oil resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

31.375 inches and 31.750 inches

Flange Style:

Double oval (sae split type flange) 2nd end

Thread Series Designator:

Un 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0