## NSN 4720-00-914-2205



Nonmetallic Hose Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4720-00-914-2205 **Cross Sectional Shape:** Round **Inside Diameter:** 1.000 inches **Tempurature Rating:** -25.0 degrees fahrenheit single response **Outside Diameter:** 1.437 inches **Quick Disconnect Size:** 1.000 inches 1st end **Connection Style:** Cam or lever (internal) 1st end **End Connection Design:** Straight 1st end **Connection Type:** Internal quick disconnect 1st end **Features Provided:** Electrostatic discharge capability **Burst Test Pressure:** 200.0 pounds per square inch **Layer Composition And Location:** 1st layer rubber impregnated fabric and outer layer molded rubber, chloroprene **Maximum Operating Pressure:** 50.0 pounds per square inch **Hydrostatic Test Pressure:** 100.0 pounds per square inch **Inside Surface Condition:** Smooth **Measuring Method And Length:** 240.000 inches excluding end fittings **Special Features:** Couplings banded to hose w/two clamps on each end **Specification Data:** 81349-mil-h-11588 government specification **Specification Or Standard:** 1 type and 1 class Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** 

No

## NSN 4720-00-914-2205

Nonmetallic Hose Assembly - Page 2 of 2



Fiig:

A542a0

Mil-std (military Standard):

Mil-prf-11588 spec.