NSN 4720-00-914-9409

Fuel/oil, hydrocarbon single response

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-914-9409

Cross Sectional Shape:
Round
Thread Class:
2b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.875 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 300.0 degrees fahrenheit single response
Outside Diameter:
1.203 inches
Minimum Inside Bending Radius:
7.380 inches
Exterior Color:
Black
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 2nd end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
1500.0 pounds per square inch
Layer Composition And Location:
1st layer rubber impregnated fabric and 2nd layer rubber impregnated braided steel wire and outer layer rubber impregnated fabric
Maximum Operating Pressure:
375.0 pounds per square inch
Thread Size:
0.750 inches 2nd end
Seat Angle:
30.0 degrees 1st end
Hydrostatic Test Pressure:
750.0 pounds per square inch
Outer Covering Environmental Protection:
Oil resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
21.250 inches
Media For Which Designed:

NSN 4720-00-914-9409

Nonmetallic Hose Assembly - Page 2 of 2



Thread	Series	Design	nator:
	0000	_00.9.	

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0