

View Online at <https://aerobasegroup.com/nsn/4720-00-916-1883>

**Cross Sectional Shape:**

Round

**Inside Diameter:**

1.500 inches

**Temperature Rating:**

-58.0 degrees fahrenheit single response and 100.0 degrees fahrenheit single response

**Outside Diameter:**

2.000 inches

**Hose Or Tubing Specification/std Data:**

Mil mil-h-11588, size 1-1/2 in. Specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**First End Fitting Specification/std Data:**

Mil mil-c-27487, type 6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Second End Fitting Specification/std Data:**

Mil mil-c-27487, type 2 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Quick Disconnect Size:**

2.000 inches 2nd end

**Connection Style:**

Cam or lever (external) 2nd end

**End Connection Design:**

Straight 2nd end

**End Fitting Component And Material:**

Complete fitting aluminum alloy all ends

**Fitting Component And Surface Treatment:**

Complete fitting anodize 1st end

**Connection Type:**

Internal quick disconnect 1st end

**Features Provided:**

Electrostatic discharge capability

**Second End Relationship With First End:**

Not identical

**Burst Test Pressure:**

200.0 pounds per square inch

**First End Swivel Action Capability:**

Not included

**Layer Composition And Location:**

Outer layer molded rubber err-100

**Maximum Operating Pressure:**

50.0 pounds per square inch

**Hydrostatic Test Pressure:**

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

600.000 inches working

**Second End Swivel Action Capability:**

Not included

**Special Features:**

Internal end connection furnished w/dust plug, external end connection furnished w/dust cap

**Media For Which Designed:**

Fuel/oil, hydrocarbon single response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A542a0