

View Online at <https://aerobasegroup.com/nsn/4720-00-916-1883>

Cross Sectional Shape:

Round

Inside Diameter:

1.500 inches

Temperature Rating:

-58.0 degrees fahrenheit single response and 100.0 degrees fahrenheit single response

Outside Diameter:

2.000 inches

Hose Or Tubing Specification/std Data:

Mil mil-h-11588, size 1-1/2 in. Specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

First End Fitting Specification/std Data:

Mil mil-c-27487, type 6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Second End Fitting Specification/std Data:

Mil mil-c-27487, type 2 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Quick Disconnect Size:

2.000 inches 2nd end

Connection Style:

Cam or lever (external) 2nd end

End Connection Design:

Straight 2nd end

End Fitting Component And Material:

Complete fitting aluminum alloy all ends

Fitting Component And Surface Treatment:

Complete fitting anodize 1st end

Connection Type:

Internal quick disconnect 1st end

Features Provided:

Electrostatic discharge capability

Second End Relationship With First End:

Not identical

Burst Test Pressure:

200.0 pounds per square inch

First End Swivel Action Capability:

Not included

Layer Composition And Location:

Outer layer molded rubber err-100

Maximum Operating Pressure:

50.0 pounds per square inch

Hydrostatic Test Pressure:

Inside Surface Condition:

Smooth

Measuring Method And Length:

600.000 inches working

Second End Swivel Action Capability:

Not included

Special Features:

Internal end connection furnished w/dust plug, external end connection furnished w/dust cap

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0