NSN 4720-00-916-1901

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-916-1901

| Cross Sectional Shape: |
|--|
| Round |
| Thread Direction: |
| Right-hand 1st end |
| Inside Diameter: |
| 0.250 inches |
| Tempurature Rating: |
| -40.0 degrees fahrenheit single response |
| Outside Diameter: |
| 0.562 inches |
| Connection Style: |
| Plain 1st end |
| End Connection Design: |
| Straight 1st end |
| Connection Type: |
| Threaded external pipe 1st end |
| Burst Test Pressure: |
| 1000.0 pounds per square inch |
| Layer Composition And Location: |
| 1st layer woven fabric and outer layer molded rubber |
| Maximum Operating Pressure: |
| 200.0 pounds per square inch |
| Thread Size: |
| 0.250 inches 1st end |
| Hydrostatic Test Pressure: |
| 400.0 pounds per square inch |
| Outer Covering Environmental Protection: |
| Oil resistant and ozone resistant and light resistant and cold resistant |
| Inside Surface Condition: |
| Smooth |
| Measuring Method And Length: |
| 180.000 inches excluding end fittings |
| Special Markings: |
| Pneumatic |
| Media For Which Designed: |
| Air single response |
| Thread Series Designator: |
| Npt 1st end |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

--

NSN 4720-00-916-1901

Nonmetallic Hose Assembly - Page 2 of 2



Demilitarization:

No

Fiig:

A542a0