## NSN 4720-00-916-1985

**Cross Sectional Shape:** 

Round

Thread Class: 3b 1st end

Thread Direction:
Right-hand 1st end
Inside Diameter:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-916-1985

0.188 inches
Tempurature Rating:
-100.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response
Outside Diameter:
0.312 inches
Minimum Inside Bending Radius:
2.000 inches
Connection Style:
Swivel nut flare 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Electrostatic discharge capability
Burst Test Pressure:
12000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
1000.0 pounds per square inch
Thread Size:
0.438 inches 1st end
Seat Angle:
37.0 degrees 2nd end
Flow Angle:
45.0 degrees 2nd end
Inside Surface Condition:
Smooth
Measuring Method And Length:
62.000 inches working
Thread Series Designator:
Unf 2nd end
Shelf Life:
N/a

## NSN 4720-00-916-1985

Nonmetallic Hose Assembly - Page 2 of 2



	Of			

--

Demilitarization:

No

Fiig:

A542a0