NSN 4720-00-917-0802

20.800 inches and 21.040 inches

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-917-0802

Cross Sectional Shape:				
Round				
Thread Class:				
2b 1st end				
Thread Direction:				
Right-hand 1st end				
Inside Diameter:				
0.125 inches				
Tempurature Rating:				
-65.0 degrees fahrenheit and 100.0 degrees fahrenheit single response				
Outside Diameter:				
Between 0.470 inches and 0.500 inches				
Minimum Inside Bending Radius:				
5.000 inches				
Exterior Color:				
Black				
Connection Style:				
Swivel nut flare 1st end				
End Connection Design:				
Straight 1st end				
Connection Type:				
Threaded internal tube 1st end				
Thready Qty Per Inch (tpi):				
24 2nd end				
Burst Test Pressure:				
4000.0 pounds per square inch				
Layer Composition And Location:				
1st layer braided fabric and 2nd layer braided fabric and outer layer molded rubber, chloroprene				
Maximum Operating Pressure:				
1000.0 pounds per square inch				
Thread Size:				
0.438 inches 2nd end				
Seat Angle:				
45.0 degrees 2nd end				
Hydrostatic Test Pressure:				
2000.0 pounds per square inch				
Flow Angle:				
45.0 degrees 2nd end				
Inside Surface Condition:				
Smooth				
Measuring Method And Length:				

NSN 4720-00-917-0802

Nonmetallic Hose Assembly - Page 2 of 2



_		•	_	
1	hread	Series	1)66	ignator:
•	mcaa	OCI ICS	D C3	igilatoi.

Uns 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0