NSN 4720-00-917-2187

Cross Sectional Shape:

Round

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-917-2187

Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.875 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response
Outside Diameter:
1.109 inches
Minimum Inside Bending Radius:
7.300 inches
Exterior Color:
Natural
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Electrostatic discharge capability
Electrostatic discharge capability Thready Qty Per Inch (tpi):
Thready Qty Per Inch (tpi):
Thready Qty Per Inch (tpi): 12 1st end
Thready Qty Per Inch (tpi): 12 1st end Burst Test Pressure:
Thready Qty Per Inch (tpi): 12 1st end Burst Test Pressure: 5000.0 pounds per square inch
Thready Qty Per Inch (tpi): 12 1st end Burst Test Pressure: 5000.0 pounds per square inch Layer Composition And Location:
Thready Qty Per Inch (tpi): 12 1st end Burst Test Pressure: 5000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire
Thready Qty Per Inch (tpi): 12 1st end Burst Test Pressure: 5000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure:
Thready Qty Per Inch (tpi): 12 1st end Burst Test Pressure: 5000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1250.0 pounds per square inch
Thready Qty Per Inch (tpi): 12 1st end Burst Test Pressure: 5000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1250.0 pounds per square inch Thread Size:
Thready Qty Per Inch (tpi): 12 1st end Burst Test Pressure: 5000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1250.0 pounds per square inch Thread Size: 1.312 inches 1st end
Thready Qty Per Inch (tpi): 12 1st end Burst Test Pressure: 5000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1250.0 pounds per square inch Thread Size: 1.312 inches 1st end Seat Angle:
Thready Qty Per Inch (tpi): 12 1st end Burst Test Pressure: 5000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1250.0 pounds per square inch Thread Size: 1.312 inches 1st end Seat Angle: 37.0 degrees 1st end
Thready Qty Per Inch (tpi): 12 1st end Burst Test Pressure: 5000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1250.0 pounds per square inch Thread Size: 1.312 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure:
Thready Qty Per Inch (tpi): 12 1st end Burst Test Pressure: 5000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1250.0 pounds per square inch Thread Size: 1.312 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 2500.0 pounds per square inch
Thready Qty Per Inch (tpi): 12 1st end Burst Test Pressure: 5000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1250.0 pounds per square inch Thread Size: 1.312 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 2500.0 pounds per square inch Inside Surface Condition:

NSN 4720-00-917-2187

Nonmetallic Hose Assembly - Page 2 of 2



Thread Series Designator:
Un 1st end
Specification Data:
96906-ms8000-800a government standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A542a0