Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-917-2189

	ross Sectional Shape:
	ound
	hread Class:
	b 1st end
	hread Direction:
	ight-hand 1st end
	side Diameter:
	875 inches
0	utside Diameter:
1	109 inches
С	onnection Style:
S	wivel nut flare 1st end
Ε	nd Connection Design:
S	traight 1st end
С	onnection Type:
т	hreaded internal tube 1st end
F	eatures Provided:
E	lectrostatic discharge capability
т	hready Qty Per Inch (tpi):
1:	2 1st end
В	urst Test Pressure:
5	000.0 pounds per square inch
L	ayer Composition And Location:
0	uter layer braided corrosion resistant steel wire
M	aximum Operating Pressure:
1:	250.0 pounds per square inch
т	hread Size:
1	312 inches 1st end
S	eat Angle:
3	7.0 degrees 1st end
Η	ydrostatic Test Pressure:
2	500.0 pounds per square inch
lr	side Surface Condition:
S	mooth
Μ	leasuring Method And Length:
4	6.200 inches working
т	hread Series Designator:
U	n 1st end
S	pecification Or Standard:
1	6 size
S	helf Life:
Ν	/a

NSN 4720-00-917-2189

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0