Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-917-2194

С	ross Sectional Shape:
R	bund
Tł	nread Class:
3b	o 1st end
Tł	nread Direction:
Ri	ght-hand 1st end
In	side Diameter:
0.	875 inches
Te	empurature Rating:
-6	5.0 degrees fahrenheit and 450.0 degrees fahrenheit single response
0	utside Diameter:
1.	109 inches
М	inimum Inside Bending Radius:
7.	375 inches
C	onnection Style:
S١	vivel nut flare 1st end
Er	nd Connection Design:
St	raight 1st end
С	onnection Type:
Tł	nreaded internal tube 1st end
Fe	eatures Provided:
EI	ectrostatic discharge capability
Tł	nready Qty Per Inch (tpi):
12	2 1st end
В	urst Test Pressure:
50	000.0 pounds per square inch
La	ayer Composition And Location:
1s	t layer braided corrosion resistant steel wire and outer layer braided corrosion resistant steel wire
M	aximum Operating Pressure:
12	250.0 pounds per square inch
Tł	nread Size:
1.	312 inches 1st end
Se	eat Angle:
37	7.0 degrees 1st end
Hy	ydrostatic Test Pressure:
25	500.0 pounds per square inch
Va	acuum In Torr:
50	).8
In	side Surface Condition:
Sr	nooth
M	easuring Method And Length:
22	2.500 inches

Nonmetallic Hose Assembly - Page 2 of 2

AeroBase Group

**Thread Series Designator:** 

Un 1st end

Specification Or Standard:

16 size

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0