## NSN 4720-00-917-2213

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-917-2213	
Cross Sectional Shape:	
Round	
Thread Class:	
3b 1st end	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.190 inches	
Tempurature Rating:	
-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response	
Outside Diameter:	
0.310 inches	
Minimum Inside Bending Radius:	
2.000 inches	
Exterior Color:	
Natural	
Connection Style:	
Swivel nut flare 2nd end	
End Connection Design:	
Straight 1st end	
Connection Type:	
Threaded internal tube 1st end	
Features Provided:	
Electrostatic discharge capability	
Burst Test Pressure:	
12000.0 pounds per square inch	
Layer Composition And Location:	
Outer layer braided corrosion resistant steel wire	
Maximum Operating Pressure:	
1500.0 pounds per square inch	
Thread Size:	
0.438 inches 1st end	
Seat Angle:	

37.0 degrees 2nd end

**Hydrostatic Test Pressure:** 

3000.0 pounds per square inch

Flow Angle:

90.0 degrees 2nd end

**Inside Surface Condition:** 

Smooth

**Measuring Method And Length:** 

7.500 inches working

## NSN 4720-00-917-2213

Nonmetallic Hose Assembly - Page 2 of 2



	•		
I hraad	Series	I Jaciui	12t∩r•
ııııcau	061163	Desidi	iatoi.

Unf 2nd end

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0