Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-917-2227

Cro	ss Sectional Shape:
Rou	-
	ead Class:
	1st end
	ead Direction:
	ht-hand 1st end
-	de Diameter:
	20 inches
-	npurature Rating:
	0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response
	side Diameter:
0.31	10 inches
Min	imum Inside Bending Radius:
	00 inches
Cor	nnection Style:
Swi	vel nut flare 2nd end
Enc	Connection Design:
Stra	aight 1st end
Cor	nnection Type:
Thre	eaded internal tube 1st end
Fea	tures Provided:
Eleo	ctrostatic discharge capability
Bur	st Test Pressure:
120	00.0 pounds per square inch
Lay	er Composition And Location:
Out	er layer braided corrosion resistant steel wire
Max	kimum Operating Pressure:
150	0.0 pounds per square inch
Thr	ead Size:
0.43	38 inches 1st end
Sea	t Angle:
37.0) degrees 2nd end
Нус	Irostatic Test Pressure:
300	0.0 pounds per square inch
Flo	w Angle:
90.0) degrees 2nd end
Insi	de Surface Condition:
Smo	poth
Mea	asuring Method And Length:
35.0	000 inches working
Thr	ead Series Designator:
Unf	2nd end

NSN 4720-00-917-2227

Nonmetallic Hose Assembly - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0

