

View Online at <https://aerobasegroup.com/nsn/4720-00-917-2229>

**Cross Sectional Shape:**

Round

**Thread Class:**

3b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.406 inches

**Temperature Rating:**

-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response

**Outside Diameter:**

0.562 inches

**Minimum Inside Bending Radius:**

4.625 inches

**Connection Style:**

Swivel nut flare 2nd end

**End Connection Design:**

Straight 1st end

**Connection Type:**

Threaded internal tube 1st end

**Features Provided:**

Reusable end fittings and electrostatic discharge capability

**Burst Test Pressure:**

8000.0 pounds per square inch

**Layer Composition And Location:**

Outer layer braided corrosion resistant steel wire

**Maximum Operating Pressure:**

1500.0 pounds per square inch

**Thread Size:**

0.750 inches 2nd end

**Seat Angle:**

37.0 degrees 2nd end

**Hydrostatic Test Pressure:**

3000.0 pounds per square inch

**Flow Angle:**

90.0 degrees 2nd end

**Outer Covering Environmental Protection:**

Corrosion resistant

**Vacuum In Torr:**

50.8

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

29.000 inches working

**Thread Series Designator:**

Unf 2nd end

**Specification Data:**

96906-ms8000 government standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiiig:**

A542a0