Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-917-2385

Cros	ss Sectional Shape:
Rour	nd
Thre	ead Class:
3b 19	st end
Thre	ad Direction:
Righ	t-hand 1st end
Insic	de Diameter:
0.62	5 inches
Tem	purature Rating:
-40.0	) degrees fahrenheit and 250.0 degrees fahrenheit single response
Oute	side Diameter:
1.078	8 inches
Mini	mum Inside Bending Radius:
6.50	0 inches
Exte	rior Color:
Natu	Iral
Con	nection Style:
Swiv	rel nut flare 1st end
End	Connection Design:
Strai	ght 2nd end
Con	nection Type:
Thre	aded internal tube 1st end
Thre	eady Qty Per Inch (tpi):
14 2r	nd end
Burs	st Test Pressure:
6000	).0 pounds per square inch
Laye	er Composition And Location:
1st la	ayer braided cotton cord and 2nd layer braided steel wire and outer layer molded rubber
Maxi	imum Operating Pressure:
1500	).0 pounds per square inch
Thre	ad Size:
1.06	2 inches 1st end
Seat	Angle:
37.0	degrees 1st end
Oute	er Covering Environmental Protection:
Abra	sion resistant and fuel resistant
Vacı	uum In Torr:
50.8	
Insic	de Surface Condition:
Smo	oth
Mea	suring Method And Length:
	00 inches excluding end fittings

Nonmetallic Hose Assembly - Page 2 of 2



## Media For Which Designed:

Air and hydraulic fluid and fuel/oil, hydrocarbon and fuel/oil, hydrocarbon and fuel/oil, hydrocarbon and water, fresh single response

Thread Series Designator:

Un 1st end

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A542a0