

View Online at <https://aerobasegroup.com/nsn/4720-00-917-3964>

**Cross Sectional Shape:**

Round

**Thread Class:**

3b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.173 inches

**Temperature Rating:**

-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response

**Outside Diameter:**

0.343 inches

**Minimum Inside Bending Radius:**

2.000 inches

**Exterior Color:**

Natural

**Connection Style:**

Swivel nut flare 2nd end

**End Connection Design:**

Straight 1st end

**Connection Type:**

Threaded internal tube 1st end

**Features Provided:**

Electrostatic discharge capability and nuts drilled for lockwire

**Burst Test Pressure:**

7000.0 pounds per square inch

**Layer Composition And Location:**

Outer layer braided corrosion resistant steel wire

**Maximum Operating Pressure:**

1500.0 pounds per square inch

**Thread Size:**

0.438 inches 1st end

**Seat Angle:**

37.0 degrees 2nd end

**Hydrostatic Test Pressure:**

3000.0 pounds per square inch

**Flow Angle:**

90.0 degrees 2nd end

**Outer Covering Environmental Protection:**

Abrasion resistant and corrosion resistant

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

8.500 inches working

**Test Data Document:**

07482-j264 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Thread Series Designator:**

Unjf 1st end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0