Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-917-4434

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
Between 0.156 inches and 0.188 inches
Tempurature Rating:
55.0 degrees fahrenheit single response and 250.0 degrees fahrenheit single response
Outside Diameter:
Between 0.312 inches and 0.328 inches
Minimum Inside Bending Radius:
2.000 inches
Exterior Color:
Natural or natural
Connection Style: Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type: Threaded internal tube 1st end
Features Provided:
Nuts drilled for lockwire
Burst Test Pressure:
12000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
3000.0 pounds per square inch
Thread Size:
0.438 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
6000.0 pounds per square inch
Outer Covering Environmental Protection:
Corrosion resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
14.375 inches and 14.625 inches

Nonmetallic Hose Assembly - Page 2 of 2



Thread Series Designator:

Unjf 1st end

Fsc Application Data:

Jet engine, aircraft

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0