Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-917-6755

Cross Section	al Shape:
Round	
Thread Class:	
3b 1st end	
Thread Direction	on:
Right-hand 1st	end
Inside Diamete	er:
0.188 inches	
Tempurature F	lating:
-45.0 degrees fa	ahrenheit single response and 450.0 degrees fahrenheit single response
Outside Diame	ter:
0.315 inches	
Minimum Insid	e Bending Radius:
2.000 inches	
Connection St	yle:
Swivel nut flare	1st end
End Connection	n Design:
Straight 1st end	
Connection Ty	pe:
Threaded interr	al tube 1st end
Burst Test Pre	ssure:
7500.0 pounds	per square inch
Layer Compos	ition And Location:
Outer layer brai	ded corrosion resistant steel wire
Maximum Ope	rating Pressure:
1500.0 pounds	per square inch
Thread Size:	
0.438 inches 1s	it end
Seat Angle:	
37.0 degrees 1	st end
Hydrostatic Te	st Pressure:
3000.0 pounds	per square inch
Inside Surface	Condition:
Smooth	
Measuring Met	hod And Length:
50.000 inches	
Thread Series	Designator:
Unef 1st end	
Shelf Life:	
N/a	
Unit Of Measu	/e:

NSN 4720-00-917-6755

Nonmetallic Hose Assembly - Page 2 of 2

Demilitarization:

No

Fiig:

A542a0

