

View Online at <https://aerobasegroup.com/nsn/4720-00-917-8373>

Cross Sectional Shape:

Round

Inside Diameter:

Between 3.938 inches and 4.062 inches

Outside Diameter:

Between 4.562 inches and 4.688 inches

First End Fitting Specification/std Data:

Milms27025-17 standard (includes industry or association standards, individual manufactureer standards, etc.).

Second End Fitting Specification/std Data:

Mil ms27021-17 standard (includes industry or association standards, individual manufactureer standards, etc.).

Quick Disconnect Size:

4.000 inches 2nd end

Connection Style:

Cam or lever (external) 2nd end

End Connection Design:

Straight 2nd end

End Fitting Component And Material:

Complete fitting aluminum alloy all ends

Fitting Component And Surface Treatment:

Complete fitting anodize 1st end

Connection Type:

Internal quick disconnect 1st end

Second End Relationship With First End:

Not identical

Burst Test Pressure:

700.0 pounds per square inch

First End Swivel Action Capability:

Not included

Layer Composition And Location:

Outer layer molded rubber, chloroprene err-100

Maximum Operating Pressure:

175.0 pounds per square inch

Hydrostatic Test Pressure:

280.0 pounds per square inch

Outer Covering Environmental Protection:

Abrasion resistant and fuel resistant and mildew resistant and oil resistant and weatherproof

Inside Surface Condition:

Smooth

Measuring Method And Length:

600.000 inches

Second End Swivel Action Capability:

Not included

Special Features:

Inner conveying tube material-rubber, synthetic

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Specification Data:

81349-mil-h-26521 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0