

View Online at <https://aerobasegroup.com/nsn/4720-00-917-8373>

**Cross Sectional Shape:**

Round

**Inside Diameter:**

Between 3.938 inches and 4.062 inches

**Outside Diameter:**

Between 4.562 inches and 4.688 inches

**First End Fitting Specification/std Data:**

Milms27025-17 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Second End Fitting Specification/std Data:**

Mil ms27021-17 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Quick Disconnect Size:**

4.000 inches 2nd end

**Connection Style:**

Cam or lever (external) 2nd end

**End Connection Design:**

Straight 2nd end

**End Fitting Component And Material:**

Complete fitting aluminum alloy all ends

**Fitting Component And Surface Treatment:**

Complete fitting anodize 1st end

**Connection Type:**

Internal quick disconnect 1st end

**Second End Relationship With First End:**

Not identical

**Burst Test Pressure:**

700.0 pounds per square inch

**First End Swivel Action Capability:**

Not included

**Layer Composition And Location:**

Outer layer molded rubber, chloroprene err-100

**Maximum Operating Pressure:**

175.0 pounds per square inch

**Hydrostatic Test Pressure:**

280.0 pounds per square inch

**Outer Covering Environmental Protection:**

Abrasion resistant and fuel resistant and mildew resistant and oil resistant and weatherproof

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

600.000 inches

**Second End Swivel Action Capability:**

Not included

**Special Features:**

Inner conveying tube material-rubber, synthetic

**Media For Which Designed:**

Fuel/oil, hydrocarbon single response

**Specification Data:**

81349-mil-h-26521 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0