

View Online at <https://aerobasegroup.com/nsn/4720-00-918-2007>

**Cross Sectional Shape:**

Round

**Thread Class:**

2b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.375 inches

**Temperature Rating:**

-40.0 degrees fahrenheit single response and 200.0 degrees fahrenheit single response

**Outside Diameter:**

0.582 inches

**Inner Conveying Tube Style:**

Helical open-pitch corrugated

**Exterior Color:**

Natural

**Connection Style:**

Swivel nut flare 1st end

**End Connection Design:**

Straight 1st end

**Connection Type:**

Unthreaded external hose 2nd end

**Features Provided:**

Nuts drilled for lockwire

**Burst Test Pressure:**

1000.0 pounds per square inch

**Layer Composition And Location:**

Outer layer braided corrosion resistant steel wire

**Maximum Operating Pressure:**

250.0 pounds per square inch

**Thread Size:**

0.562 inches 1st end

**Seat Angle:**

37.0 degrees 1st end

**Hydrostatic Test Pressure:**

500.0 pounds per square inch

**Outer Covering Environmental Protection:**

Corrosion resistant

**Measuring Method And Length:**

10.750 inches working

**Inside Diameter Hose Accommodated:**

0.812 inches 2nd end

**Special Features:**

Second end has 0.250 in. Od ventura tube inside and at an 80.0 degrees angle to an 0.888 in. Od end; ventura tube set at 50.0 degrees angle to hose

**Thread Series Designator:**

Unf 1st end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A542a0