

View Online at <https://aerobasegroup.com/nsn/4720-00-918-2007>

Cross Sectional Shape:

Round

Thread Class:

2b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.375 inches

Temperature Rating:

-40.0 degrees fahrenheit single response and 200.0 degrees fahrenheit single response

Outside Diameter:

0.582 inches

Inner Conveying Tube Style:

Helical open-pitch corrugated

Exterior Color:

Natural

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Straight 1st end

Connection Type:

Unthreaded external hose 2nd end

Features Provided:

Nuts drilled for lockwire

Burst Test Pressure:

1000.0 pounds per square inch

Layer Composition And Location:

Outer layer braided corrosion resistant steel wire

Maximum Operating Pressure:

250.0 pounds per square inch

Thread Size:

0.562 inches 1st end

Seat Angle:

37.0 degrees 1st end

Hydrostatic Test Pressure:

500.0 pounds per square inch

Outer Covering Environmental Protection:

Corrosion resistant

Measuring Method And Length:

10.750 inches working

Inside Diameter Hose Accommodated:

0.812 inches 2nd end

Special Features:

Second end has 0.250 in. Od ventura tube inside and at an 80.0 degrees angle to an 0.888 in. Od end; ventura tube set at 50.0 degrees angle to hose

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A542a0