

View Online at <https://aerobasegroup.com/nsn/4720-00-918-4832>

Cross Sectional Shape:

Round

Inside Diameter:

1.500 inches

Temperature Rating:

-65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response

Flange Thickness:

0.180 inches 1st end

Outside Diameter:

1.750 inches

Minimum Inside Bending Radius:

11.000 inches

Center To Center Distance Between Bolt Holes Along Width:

1.518 inches 1st end

Center To Center Distance Between Bolt Holes Along Length:

1.518 inches 1st end

Bolt Hole Quantity:

4 1st end

Flange Length:

3.094 inches 1st end

Flange Width:

3.094 inches 1st end

Connection Style:

Plain 1st end

Bolt Hole Diameter:

0.279 inches and 0.286 inches 1st end

End Flange Construction:

Solid 1st end

End Connection Design:

Elbow 1st end

Connection Type:

Unthreaded external hose 2nd end

Burst Test Pressure:

2000.0 pounds per square inch

Layer Composition And Location:

1st layer braided cotton cord and 2nd layer braided wire and outer layer rubber impregnated braided cotton cord

Maximum Operating Pressure:

500.0 pounds per square inch

Hydrostatic Test Pressure:

1000.0 pounds per square inch

Flow Angle:

180.0 degrees 1st end

Inside Surface Condition:

Smooth

Measuring Method And Length:

124.750 inches working and 125.500 inches working

Flange Style:

Rectangular (includes square) 1st end

Inside Diameter Hose Accommodated:

1.500 inches 2nd end

Special Features:

2nd end is a 45 degree elbow

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0