

View Online at <https://aerobasegroup.com/nsn/4720-00-918-4832>

**Cross Sectional Shape:**

Round

**Inside Diameter:**

1.500 inches

**Temperature Rating:**

-65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response

**Flange Thickness:**

0.180 inches 1st end

**Outside Diameter:**

1.750 inches

**Minimum Inside Bending Radius:**

11.000 inches

**Center To Center Distance Between Bolt Holes Along Width:**

1.518 inches 1st end

**Center To Center Distance Between Bolt Holes Along Length:**

1.518 inches 1st end

**Bolt Hole Quantity:**

4 1st end

**Flange Length:**

3.094 inches 1st end

**Flange Width:**

3.094 inches 1st end

**Connection Style:**

Plain 1st end

**Bolt Hole Diameter:**

0.279 inches and 0.286 inches 1st end

**End Flange Construction:**

Solid 1st end

**End Connection Design:**

Elbow 1st end

**Connection Type:**

Unthreaded external hose 2nd end

**Burst Test Pressure:**

2000.0 pounds per square inch

**Layer Composition And Location:**

1st layer braided cotton cord and 2nd layer braided wire and outer layer rubber impregnated braided cotton cord

**Maximum Operating Pressure:**

500.0 pounds per square inch

**Hydrostatic Test Pressure:**

1000.0 pounds per square inch

**Flow Angle:**

180.0 degrees 1st end

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

124.750 inches working and 125.500 inches working

**Flange Style:**

Rectangular (includes square) 1st end

**Inside Diameter Hose Accommodated:**

1.500 inches 2nd end

**Special Features:**

2nd end is a 45 degree elbow

**Media For Which Designed:**

Fuel/oil, hydrocarbon single response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0