Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-918-5450

Cross Sectional Shape:

Round

Thread Class:

2b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.250 inches

Tempurature Rating:

-40.0 degrees fahrenheit single response and 200.0 degrees fahrenheit single response

Outside Diameter:

Between 0.531 inches and 0.594 inches

Minimum Inside Bending Radius:

3.000 inches

Hose Or Tubing Specification/std Data:

Sae j517, 100r3, size 1/4 in. Id standard (includes industry or association standards, individual manufactureer standards, etc.).

First End Fitting Specification/std Data:

Saej516, fig.9a, table 6b, size 1/4 id, thd size -4 standard (includes industry or association standards, individual manufactureer standards, etc.).

Second End Fitting Specification/std Data:

Saej516, fig.1a, table 1c, hose size -4, thd size -4 standard (includes industry or association standards, individual manufactureer standards, etc.).

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Straight 2nd end

End Fitting Component And Material:

Complete fitting steel all ends

Fitting Component And Surface Treatment:

Complete fitting cadmium and complete fitting zinc 1st end

Connection Type:

Threaded internal tube 1st end

Second End Relationship With First End:

Not identical

Burst Test Pressure:

5000.0 pounds per square inch

First End Swivel Action Capability:

Not included

Layer Composition And Location:

Outer layer molded rubber err-100

Maximum Operating Pressure:

1250.0 pounds per square inch

Unable To Decode:

Unable to decode or unable to decode

Nonmetallic Hose Assembly - Page 2 of 2



Thread Size: 0.438 inches 1st end Seat Angle: 45.0 degrees 1st end Hydrostatic Test Pressure: 2500.0 pounds per square inch **Outer Covering Environmental Protection:** Oil resistant and weatherproof Unable To Decode: Unable to decode or unable to decode **Inside Surface Condition:** Smooth Measuring Method And Length: 18.000 inches Second End Swivel Action Capability: Not included **Special Features:** Inner conveying tube material-rubber, buna-n Media For Which Designed: Fuel/oil, hydrocarbon single response **Thread Series Designator:** Unf 1st end Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A542a0