Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-919-7266

Cross Sectional Shape:
Round
Thread Direction:
Right-hand 1st end
Inside Diameter:
2.500 inches
Tempurature Rating:
-40.0 degrees fahrenheit single response and 125.0 degrees fahrenheit single response
Outside Diameter:
3.125 inches
Minimum Inside Bending Radius:
15.500 inches
Connection Style:
Plain 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded external pipe 1st end Features Provided:
Electrostatic discharge capability Burst Test Pressure:
375.0 pounds per square inch Layer Composition And Location:
Outer layer helix steel coil
Maximum Operating Pressure:
50.0 pounds per square inch
Hydrostatic Test Pressure:
125.0 pounds per square inch
Vacuum In Torr:
127.0
Inside Surface Condition:
Smooth
Measuring Method And Length:
594.000 inches and 606.000 inches
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No

NSN 4720-00-919-7266

Nonmetallic Hose Assembly - Page 2 of 2



Fiig: A542a0 Mil-std (military Standard):

Mil-h-27516 spec.