Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-920-0075

Cross Continued Shaws
Cross Sectional Shape:
Round
Thread Class:
2b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.313 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response
Outside Diameter:
Between 0.531 inches and 0.594 inches
Minimum Inside Bending Radius:
3.000 inches
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 2nd end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
1100.0 pounds per square inch
Layer Composition And Location:
1st layer braided cotton cord and outer layer rubber impregnated braided rayon cord
Maximum Operating Pressure:
275.0 pounds per square inch
Thread Size:
0.562 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
550.0 pounds per square inch
Outer Covering Environmental Protection:
Oil resistant and weatherproof
Vacuum In Torr:
254.0
Inside Surface Condition:
Smooth
Measuring Method And Length:
9.000 inches
Thread Series Designator:
Unf 1st end

## NSN 4720-00-920-0075

Nonmetallic Hose Assembly - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A542a0

