NSN 4720-00-920-1522

Cross Sectional Shape:

Round

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-920-1522

Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.380 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
0.620 inches
Minimum Inside Bending Radius:
3.000 inches
Exterior Color:
Black
End Application:
Grumman a10 aircraft
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
1000.0 pounds per square inch
Layer Composition And Location:
1st layer braided cotton cord and outer layer molded rubber
Maximum Operating Pressure:
250.0 pounds per square inch
Thread Size:
0.625 inches 1st end
Seat Angle:
45.0 degrees 1st end
Hydrostatic Test Pressure:
500.0 pounds per square inch
Outer Covering Environmental Protection:
Water resistant and salt water resistant
Vacuum In Torr:
50.8
Inside Surface Condition:

NSN 4720-00-920-1522

Nonmetallic Hose Assembly - Page 2 of 2



Measuring Method And Length: 36.000 inches working Media For Which Designed: Air and water, fresh and water, salt single response Thread Series Designator: Unf 1st end Specification Or Standard: 6 size Shelf Life: N/a Unit Of Measure: - Demilitarization: No

Fiig: A542a0