## NSN 4720-00-922-0037

**Cross Sectional Shape:** 

Round

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-922-0037

Thread Class:		
3b 1st end		
Thread Direction:		
Right-hand 1st end		
Inside Diameter:		
0.500 inches		
Tempurature Rating:		
-65.0 degrees fahrenheit and 180.0 degrees fahrenheit single response		
Outside Diameter:		
0.781 inches		
Connection Style:		
Swivel nut flare 1st end		
End Connection Design:		
Straight 1st end		
Connection Type:		
Threaded internal tube 1st end		
Features Provided:		
Reusable end fittings		
Burst Test Pressure:		
750.0 pounds per square inch		
Layer Composition And Location:		
1st layer braided cotton cord and outer layer molded rubber		
Maximum Operating Pressure:		
150.0 pounds per square inch		
Thread Size:		
0.750 inches 1st end		
Seat Angle:		
37.0 degrees 1st end		
Hydrostatic Test Pressure:		
250.0 pounds per square inch		
Outer Covering Environmental Protection:		
Abrasion resistant and fuel resistant and oil resistant		
Vacuum In Torr:		
254.0		
Inside Surface Condition:		
Smooth		
Measuring Method And Length:		
18.000 inches working		
Media For Which Designed:		

Fuel/oil, hydrocarbon single response

## NSN 4720-00-922-0037

Nonmetallic Hose Assembly - Page 2 of 2



Thread Series	Designator:
---------------	-------------

Unjf 1st end

**Specification Data:** 

88044-an6270 government standard

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

Demilitarization:

No

Fiig:

A542a0