NSN 4720-00-922-0044

Cross Sectional Shape:

Corrosion resistant

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-922-0044

| Round |
|---|
| Thread Class: |
| 3b 1st end |
| Thread Direction: |
| Right-hand 1st end |
| Inside Diameter: |
| 0.625 inches |
| Tempurature Rating: |
| -67.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response |
| Outside Diameter: |
| 0.789 inches |
| Minimum Inside Bending Radius: |
| 6.500 inches |
| Exterior Color: |
| Natural |
| Connection Style: |
| Swivel nut flare 2nd end |
| End Connection Design: |
| Straight 1st end |
| Connection Type: |
| Threaded internal tube 1st end |
| Features Provided: |
| Electrostatic discharge capability |
| Thready Qty Per Inch (tpi): |
| 12 2nd end |
| Burst Test Pressure: |
| 5000.0 pounds per square inch |
| Layer Composition And Location: |
| Outer layer braided corrosion resistant steel wire |
| Maximum Operating Pressure: |
| 1000.0 pounds per square inch |
| Thread Size: |
| 1.062 inches 2nd end |
| Seat Angle: |
| 37.0 degrees 2nd end |
| Hydrostatic Test Pressure: |
| 2000.0 pounds per square inch |
| Flow Angle: |
| 90.0 degrees 2nd end |
| Outer Covering Environmental Protection: |

NSN 4720-00-922-0044

Nonmetallic Hose Assembly - Page 2 of 2



| vacuum in Torr: |
|------------------------------|
| 50.8 |
| Inside Surface Condition: |
| Smooth |
| Measuring Method And Length: |
| 11.250 inches working |
| Thread Series Designator: |
| Unj 2nd end |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig: A542a0