

View Online at <https://aerobasegroup.com/nsn/4720-00-922-1368>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.256 inches

Temperature Rating:

-65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response

Outside Diameter:

0.875 inches

Minimum Inside Bending Radius:

5.000 inches

Exterior Color:

Natural

Angle Between Rigid Elbow Fittings In Deg:

77.0

Connection Style:

Swivel nut, flareless 2nd end

End Connection Design:

Elbow 2nd end

End Fitting Component And Material:

Complete fitting steel comp 304 all ends

Fitting Component And Surface Treatment:

Complete fitting passivate 1st end

Connection Type:

Threaded internal tube 1st end

Features Provided:

Electrostatic discharge capability

Second End Relationship With First End:

Not identical

Burst Test Pressure:

16000.0 pounds per square inch

First End Swivel Action Capability:

Not included

Layer Composition And Location:

Outer layer braided corrosion resistant steel wire err-100

Maximum Operating Pressure:

3000.0 pounds per square inch

Thread Size:

0.562 inches 2nd end

Seat Angle:

12.0 degrees 2nd end

Hydrostatic Test Pressure:

6000.0 pounds per square inch

Flow Angle:

90.0 degrees 2nd end

Outer Covering Environmental Protection:

Corrosion resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

32.750 inches working

Second End Swivel Action Capability:

Not included

Special Features:

Inner conveying tube material-plastic, polytetrafluoroethylene

Supplementary Features:

This item has been reviewed for asbestos material; the current approved sources, 00624 have indicated their part number contained asbestos prior to 1984, they continue to manufacture the same part number without asbestos material after 1984

Thread Series Designator:

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0