## NSN 4720-00-922-1375

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-922-1375
Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.750 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response
Outside Diameter:
1.075 inches
Minimum Inside Bending Radius:
3.750 inches
Connection Style:
Swivel nut, flareless 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Electrostatic discharge capability
Thready Qty Per Inch (tpi):
12 2nd end
Burst Test Pressure:
3600.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
1000.0 pounds per square inch
Thread Size:
1 062 inches 2nd end

Seat Angle:

12.0 degrees 2nd end

**Hydrostatic Test Pressure:** 

1800.0 pounds per square inch

Flow Angle:

45.0 degrees 2nd end

**Outer Covering Environmental Protection:** 

Corrosion resistant

**Inside Surface Condition:** 

Convoluted

## NSN 4720-00-922-1375

Nonmetallic Hose Assembly - Page 2 of 2



<b>Measuring Method And Length:</b>
39.000 inches working
Media For Which Designed:
Fluid single response
Thread Series Designator:
Un 2nd end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

**Fiig:** A542a0